

CITY OF NORMAN
Office of the Purchasing Agent
Norman, Oklahoma

FORM FOR BIDDERS NO. 0809-81

Opening of Bids
City of Norman
Purchasing
P.O. Box 370
Norman, Oklahoma 73070

Bid Opening:
2:00 P.M.
May 7, 2009

Dear Sir:

The undersigned bidder declares that before preparing this bid he read carefully the detailed specifications and that his bid is made with full knowledge of the kind, quality, and quantity of the materials or services to be furnished.

The undersigned bidder offers and proposes to furnish the materials, equipment, or other services hereinafter set forth, in the manner and under the conditions and in accordance with the specifications on file in the Office of the Purchasing Agent, at the following prices:

One (1) new and unused steel open top live floor trailer _____

TOTAL NET DELIVERY PRICE \$
(less all taxes)

AFFIDAVIT OF NON-COLLUSION

STATE OF _____)

COUNTY OF _____)

_____, of lawful age, being first duly sworn, on oath says, that (s)he is the agent authorized by the bidder to submit the attached bid. Affiant further states that the bidder has not been a party to any collusion among bidders in restraint to freedom of competition by agreement to bid at a fixed price or to refrain from bidding; or with any city official or employee as to quantity, quality, or price in the prospective contract, or any other terms of prospective contract; or in any discussion between bidders and any city official concerning exchange of money or other thing of value for special consideration in the letting of a contract; that the bidder/contractor has not paid, given or donated or agreed to pay, give or donate to any officer or employee of the City of Norman, Oklahoma any money or other thing of value, either directly or indirectly, in the procuring of the award of a contract pursuant to this bid.

Bidder
By:

Subscribed and sworn to before me on this _____ day of _____, 20_____.

_____ My commission expires

CITY OF NORMAN April 9, 2009
Office of the Purchasing Division
Norman, Oklahoma

INVITATION TO BID #0809-81

The City of Norman, Oklahoma will open sealed bids in the Conference Room of Building C, City of Norman on the below listed item at 2:00 P.M. on Thursday, May 7, 2009.

One (1) new and unused steel open top live floor trailer

All bids **must** be in the Office of the Purchasing Division, 201-C West Gray St., Norman, Oklahoma, 73069, **BEFORE THE FINAL CLOSING HOUR** as shown on the Invitation to Bid. If bid is mailed, to be considered it **should** be addressed as follows: Attention: Purchasing Division, Opening of Bids, City of Norman, P.O. Box 370, Norman, Oklahoma, 73070. In addition, the bid envelope **should** be plainly marked on both sides indication the bid number.

The unit price **must be stated** on all items and all totals extended, if required. **BIDDER GUARANTEES UNIT PRICE TO BE CORRECT.** To receive consideration, bids **must** be submitted on the City of Norman "Form for Bidders" and "Bidders Proposal" (if applicable), which are hereby made part of this Invitation to Bid.

Alternate bids may be considered. If bidding an alternate, so state on the face of the Form for Bidders and fully describe the merchandise and include Manufacturer's literature. Unless the bidder identifies on the Form for Bidders that an alternate is being bid, the vendor **will be expected** to deliver merchandise as specified. Alternate bids **shall not** be submitted to circumvent the specifications.

The Affairs of the City of Norman, whether in the conduct of its governmental or proprietary functions, involve the health, safety, and welfare of the public; and because the item(s) specified are necessary and proper for the conduct of said affairs, any delay in the delivery of the item(s) being bid can jeopardize the health, safety, and welfare of the public, and can result in the incurring of additional expenses to the City. For these reasons, it is understood by the bidder the date of delivery of the item(s) being bid herein is considered to be an integral part of this bid and may be considered in awarding the contract.

Discount and delivery date **must** be plainly stated on the Form for Bidders and Bidders Proposal. Use ink pen or typewriter in filling in quotation and initial any corrections. Bid and Affidavit **must** be signed in ink by an authorized representative of the company making the bid. Bidders **should** submit one original and one duplicate Form for Bidders and Proposals. All bids **will** be awarded by Section of Sections whichever is in the best interest of the City. Any bidder who fails to return the third consecutive invitation **will be removed** from the bid list. If the above procedures are not followed, bids may be disqualified. The right is reserved by the City to reject any or all bids or parts of bids. All bids are public records and are available during regular business hours.

	type with parking brake feature. Glad hand couplers located at front of trailer. Automatic slack adjusters	_____
WHEELS	10 Stud budd	_____
RIMS	8.25" x 22.5" Steel disc	_____
TIRES	11R22.5 14 ply radials load range H Goodyear Duraseal G287MSA	_____
5th WHEEL PLATE	3/8" Hi-tensil steel	_____
	2 7/8" Kingpin, 48" height, KP 36" back	_____
	4X4 tubing framework with 2X4 reinforcing	_____
LANDING GEAR	Two speed 220,000# static load, 50,000# lift, with sand shoes	_____
	3/16" H-tensil steel wing type mounting plates	_____
	wide spread design	_____
<u>BODY</u>		
SIDES	12 gauge Hi-tensil steel (50,000# minimum yield)	_____
	outside dirt shedders between each side stake	_____
	Tarp hooks on every other side post to be mounted street side	_____
SIDE POSTS	6" X 3 1/2" X 12 gauge Hi-tensil (50,000# minimum yield) on 24" centers	_____
TOP RAIL	4" X 6" X 3/16" structural tubing (50,000# yield)	_____

BOTTOM RAIL	10 gauge X 4 1/2" with 2" X 3" X 3/16" tubing inside (50,000# yield)	<hr/>
REAR POST	16" X 4 1/2" X 1/4", extend 18" below rub rail	<hr/>
BULK HEAD	12 gauge Hi-tensil (50,000# minimum) 2 vertical braces - 11 gauge 2" X 3" tubing and 4 horizontal braces - 11 gauge 2" X 3" tubing	<hr/>
	Minimum of 1 front cleanout door, top hinged with latches for cleanout and maintenance	<hr/>
	top cap minimum of 1/4" steel plate with one cross support at rear of cap 2" X 3" X 1/4" tubing and one center cross support of 2" X 3" X 1/4" tubing, welded construction	<hr/>
TAILGATE	12 gauge Hi-tensil (50,000# yield) 1/4" X 3" X 4" rectangular tubing frame with two horizontal braces	<hr/>
	Manual positive cam lock rear closing system with three heavy duty latches located on street side	<hr/>
	6 individual hinges with replaceable hinge pins with factory installed grease fittings located on curb side of trailer	<hr/>
	Door retainer chain and brackets to hold door open	<hr/>
LADDERS	located on driver's side of bulkhead with cat-walk and center of tailgate	<hr/>

PUSH BUMPER located at center rear of trailer
 4" X 8" X 3/8" with 3/4" shackle plate _____
 bumper tied to main frame _____
 OPTIONAL - toe shackle _____

MUD FLAPS Clearview spray suppressant type _____

LIGHTING D.O.T. approved LED type rubber mount
 sealed beam Truck-lite lights with manufactured
 wiring harness _____
 Lights mounted in bottom of tailgate away
 from
 discharge of refuse. Bolt on gaurds to
 surround
 lights to prevent damage when backing _____
 Reflective tape to meet all D.O.T. standards _____
 7-way 12 volt plug at front of trailer _____

WELDING Side posts and seams must be continuously
 welded _____

PAINT Conform to SSPC-SP1 and SSPC-SP3
 standards _____
 One coat of rust inhibitor primer with two
 coats
 of industrial enamel finish _____
 Olympic White color _____

FLOOR

CROSS MEMBERS 4" Jr. I-beam (80,000# tensile) on 12"
 centers _____
 every other cross member gusseted to the
 main
 frame with 3/16" gussets _____

SUB-DECK	Steel 16 gauge tubing	
DECKING	To be 6061-T6 extruded aluminum with triple ridge deck	
DECK MOUNTING	To be bolted to the cross drives with no less than 4 3/8" diameter allen type counter sunk, grade 8 deck bolts with spring lock nuts	
REAR DOWN HOLDS	Block to be mounted at the discharge end of trailer machined from UHMW material	
BEARINGS	Deck bearings to be installed at 30 bearings per linear foot of trailer providing 260 square inches of bearing surface per linear foot and made of high-density polyethylene	
FLOOR	To be Hallco triple ridge Type 35 or approved equivalent	
SLOPE SHEET	Located at front of trailer. 1 X 2" framework covered by 10 gauge sheet steel	
FLOORS	1' X 2' UHMW bearing next to floor surface full width of trailer Include Hold-downs at rear and 2' wear stripe	

WARRANTY

Please state any warranty

OPTIONS

- 1. Cramero Roll-off tarp or equivalent, mounted and ready to use _____
- 2. Mountain Tarp Side Flip System - electric/hydraulic automatic tarping system to include automatic lock on the rear _____

ONE (1) NEW AND UNUSED STEEL OPEN TOP LIVE FLOOR TRAILER \$ _____

LESS TRADE-INS: (\$ _____)

TOTAL NET DELIVERY PRICE
(LESS ALL TAXES) _____

SIGNED: _____ COMPANY NAME: _____

ADDRESS: _____

PHONE: _____ FAX: _____

These specifications have been reviewed and approved by:

Mike White, Fleet Management Superintendent

VENDOR LIST

B & C Body Company

3611 Irving Boulevard/75247

Dallas, TX 75356-9040

Attention

: Jim Barnett

Phone: (214) 631-4170

Fax: (214) 630-0852

J & R Equipment

25-C North Council

OKC, OK 73127

Attention

: Mark Womack

Phone: 495-5110

Fax: 495-5112

Sooner Great Dane

5204 West I-40 Service Road

OKC, OK 73128

Attention

: Sales

Phone: 946-9907

Fax: 943-7458

Steco

PO Box 3127

Enid, OK 73702

Attention

: Brian Henrichs

Phone: (800) 627-8326

Fax: (580) 242-1635

Southwest Trailers & Equipment

10400 West Reno

OKC. OK 73127

Attention

: Wade Scarberry

Phone: 943-9851

Fax: 943-4013